



# INP-75A0033MIA

SKU: 234751



Netzwerk Dome, PTZ, 33x 2952x1944, Tag/Nacht, WDR, AI Alarm, Audio, 24/12V, PoE, IP66

## Main Features

1/2.7" CMOS sensor, maximum resolution 5 MP/30fps

AI analysis functions including object classification

WDR 120dB, 3D-DNR Noise Reduction

Motorized autofocus zoom lens 33x 4.3-142mm

Smart Codec H.265/H.264, multi-streaming

Browser independent (IE, Edge, Safari, Firefox, Chrome)

Supports ONVIF Profile S and Profile T

Local storage via Micro SD card

Audio input and output

Power supply 12VDC, 24VAC or PoE IEEE 802.3at

IR LED illumination, IP66

Wall bracket included

## Specifications

Dimensions (HxWxD)	206,4×351,8mm
Series	eneo IN-Series
Camera Type	Face recognition, People Count, Retail Intelligence
Resolution Standard	5 Megapixel
System	True Day&Night
Sensor size	1/2.7"
Imager	CMOS
Video compression	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG
Image resolution max.	2592x1944
Image Transmission Rate	30 fps

# INP-75A0033MIA

## Continuation of the specifications

Day&Night switch	ICR
Sensitivity	0,003 Lux at F1,6
Low Speed Shutter	yes
Digital Noise Reduction	yes
Backlight Compensation	BLC, HLC
Wide Dynamic Range (WDR)	WDR 120dB
Motion Detector	yes
Lens Type	auto focus zoom
Focal Length	4,3 - 142 mm
Iris Control	DC
Zoom Factor	33x
Observe (62 px/m)	35,6 - 1107,3 m
Recognize (125 px/m)	17 - 548,3 m
Identify (250 px/m)	7,5 - 273,3 m
Detect (25px/m)	90,2 - 2728,4 m
Horizontal Angle of View	55 - 2,3°
Vertical Angle of View	41,6 - 1,7°
Illumination	Infrared
Housing	Outdoor
Color (housing)	black, Pantone P 179-1, RAL9003
Housing material	Aluminium
Heater	no
Blower	no
Rotation range	360°
Speed (manual)	200°/Sek.
Speed (preset)	200°/Sek.
Alarm inputs	nein
Alarm outputs	no
Audio support	yes
Ethernet interface	100Base-TX, 10Base-T
Serial interfaces	Ethernet
Internal storage	256GB, microSDHC card, microSDXC card
Analysis functions	Cross Counting (CC), Face Detection (FD), Face Recognition (FR), Heat Map (HM), Human&Vehicle Detection (PD&VD), Line Crossing Detection (LCD), Perimeter Intrusion Detection (PID), Stationary Object Detection (SOD), Tampering Detection (TD)
Mounting	Wall mount
Supply voltage	12VDC, PoE+
Power consumption	25,5W
Power over Ethernet	IEEE 802.3at
Vandal proof	no

# INP-75A0033MIA

Continuation of the specifications

Operating temperature	-30°C ~ +60°C, @ Humidity 90% or less (non-condensing)
ONVIF	ONVIF Profile G, ONVIF Profile S, ONVIF Profile T
Protection rating	IP66
Camera type	PTZ
Audio	1/1 Line input and output, 2 Way Audio
Remote configuration	Browser
Illumination range	approx. 150m
Weight	3.7kg
Manufacturer order number	234751

## Optional Accessory

SKU	Name	Description
235562	CM-22	Corner mounting adapter for wall bracket WB-24 and PTZ dome camera INP-75A0033MIA
236198	eneo INsight Installation Tool	Supports adjustments for cameras with AI features for IN-series
234990	eneo INsight mobile	Mobile App for recorder IN- and MN-series
218218	eneo Site Manager	Management Software for eneo IP products
235257	PM-21	Pole mounting adapter for camera connection box AK-20 and AK-21

## Optional Services

SKU	Name	Description
229234	CON-KAM-IPKON	Preconfiguration 1x IP camera Function test, FW update

# INP-75A0033MIA

## Your contact person

VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Germany

