



# INB-55M2713M0A

SKU: 234993

EAN: 4260229840078



Network Camera Bullet, 2592x1944, Day/Night, WDR, AI 2,7-13,5mm, IR, 12V, PoE, IP67

## Main Features

1/2.7" CMOS sensor, 5 MP/30fps

AI analysis functions including object classification

WDR 120dB, 3D-DNR Noise Reduction

Motorized varifocal lens 2.7-13.5mm

Smart Codec H.265/H.264, multi-streaming

Browser independent (IE, Edge, Safari, Firefox, Chrome)

Supports ONVIF Profile S and Profile T

Multilingual menu navigation (OSD)

Local storage via Micro SD card

Supports audio and external alarm input and output

Power supply 12VDC or PoE IEEE 802.3af

IR LED illumination, IP67

## Specifications

|                     |  |
|---------------------|--|
| Dimensions (HxWxD)  | 83,88x87,4x242mm   |
| Series              | eneo IN-Series   |
| Camera Type         | Face recognition, License plate recognition, People Count, Retail Intelligence |
| Resolution Standard | 5 Megapixel  |
| System              | True Day&Night   |
| Sensor size         | 1/2.7"   |
| Imager              | CMOS   |
| Video compression   | H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG             |

# INB-55M2713M0A

## Continuation of the specifications

|                               |   |
|-------------------------------|---|
| Image resolution max.         | 2592x1944   |
| Image Transmission Rate       | 30 fps  |
| Day&Night switch              | ICR   |
| Sensitivity                   | 0,003 Lux at F1,6   |
| Low Speed Shutter             | yes   |
| Digital Noise Reduction       | yes   |
| Backlight Compensation        | BLC, HLC  |
| Wide Dynamic Range (WDR)      | WDR 120dB   |
| Motion Detector               | yes   |
| Lens Type                     | Varifocal (motorized)   |
| Focal Length                  | 2,7 - 13,5 mm   |
| Iris Control                  | DC  |
| Zoom Factor                   | 4x  |
| Digital Zoom                  | yes   |
| Observe (62 px/m)             | 24,3 - 104,5 m  |
| Recognize (125 px/m)          | 11,5 - 52,2 m   |
| Identify (250 px/m)           | 5,2 - 25,6 m  |
| Detect (25px/m)               | 62,5 - 260,3 m  |
| Horizontal Angle of View      | 102 - 31°   |
| Vertical Angle of View        | 73 - 23°  |
| MOD (Minimum Object Distance) | 0,3 m   |
| Illumination                  | Infrared  |
| Housing                       | Outdoor   |
| Color (housing)               | Pantone P 179-1, RAL9003  |
| Housing material              | Aluminium   |
| Heater                        | no  |
| Blower                        | no  |
| Video outputs                 | no  |
| Alarm inputs                  | 1   |
| Alarm outputs                 | 1   |
| Audio support                 | yes   |
| Ethernet interface            | 100Base-TX, 10Base-T  |
| Serial interfaces             | Ethernet  |
| Internal storage              | 256GB, microSDHC card, microSDXC card   |
| Analysis functions            | Attribute Detection (AD), Cross Counting (CC), Crowd Density Detection (CD), Face Attendance (FA), Face Detection (FD), Face Recognition (FR), Heat Map (HM), Human&Vehicle Detection (PD&VD), License Plate Detection (LPD), License Plate Recognition (LPR), Line Crossing Detection (LCD), Perimeter Intrusion Detection (PID), Queue Length Detection (QD), Rare Sound Detection (RSD), Stationary Object Detection (SOD) |

# INB-55M2713M0A

Continuation of the specifications

|                           |  |
|---------------------------|--|
| Mounting                  | Ceiling mount, Wall mount                              |
| Supply voltage            | 12VDC, PoE   |
| Power consumption         | 4.5W   |
| Power over Ethernet       | IEEE 802.3af   |
| Vandal proof              | no   |
| Operating temperature     | -35°C ~ +55°C, @ Humidity 90% or less (non-condensing) |
| ONVIF                     | ONVIF Profile G, ONVIF Profile S, ONVIF Profile T      |
| Protection rating         | IP67   |
| Camera type               | Bullet   |
| Audio                     | 1/1 Line input and output, 2 Way Audio                 |
| Remote configuration      | Browser  |
| Illumination range        | approx. 45m  |
| Weight                    | 680g   |
| Manufacturer order number | 234993   |
| EAN/GTIN                  | 4260229840078  |

## Optional Accessory

| SKU    | Name                           | Description   |
|--------|--------------------------------|---|
| 233754 | AK-20                          | Camera connection box for Wall and ceiling mounting, IN Series Bullet Cameras |
| 233775 | AK-21                          | Camera connection box for Wall and ceiling mounting, IN Series Bullet Cameras |
| 235339 | AK-24                          | Dual camera connection box for Bullet or Fix Dome IN-Series cameras           |
| 236198 | eneo INsight Installation Tool | Supports adjustments for cameras with AI features for IN-series               |
| 234990 | eneo INsight mobile            | Mobile App for recorder IN- and MN-series                                     |
| 218218 | eneo Site Manager              | Management Software for eneo IP products                                      |
| 235257 | PM-21                          | Pole mounting adapter for camera connection box AK-20 and AK-21               |
| 235340 | WB-24                          | Wall bracket for Dual camera connection box AK-24                             |

## Optional Services

| SKU    | Name          | Description  |
|--------|---------------|--|
| 229234 | CON-KAM-IPKON | Preconfiguration 1x IP camera Function test, FW update |

# INB-55M2713M0A

## Your contact person

VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark  
Germany

