



INB-58F0002M0PA

SKU: 238642



Network Bullet Camera, 180° Panorama, 3840x2160, 2.0mm AI, WDR, PoE, 12V, IP67

Main Features

- 1/2.8" Sony STARVIS CMOS sensor,
- Maximum resolution 3840x2160 pixels, 20fps
- Panorama ultra wide-angle camera 180° HFoV
- AI analysis functions including object classification
- WDR and 3D-DNR noise reduction
- Lens 2.0mm fixed focal length

- Smart codec H.265/H.264, multi-streaming
- Browser-independent (Edge, Safari, Firefox, Chrome)
- Supports ONVIF profiles S/T/G and audio
- Local storage via micro SD card
- Power supply 12VDC or PoE IEEE 802.3af
- Integrated IR and white light LED illumination, IP67

Specifications

Dimensions (HxWxD)	95x241,3mm
Series	eneo IN-Series
Camera Type	Multidirektional Kamera, People Count, Retail Intelligence
Resolution Standard	8 Megapixel
System	True Day&Night
Sensor size	1/2.8"
Imager	CMOS
Video compression	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG
Image resolution max.	3640x2160

INB-58F0002M0PA

Continuation of the specifications

Image Transmission Rate	25 fps
Day&Night switch	ICR
Sensitivity	0,007 Lux bei F1,0
Low Speed Shutter	yes
Digital Noise Reduction	yes
Backlight Compensation	BLC, HLC
Wide Dynamic Range (WDR)	WDR 120dB
Motion Detector	yes
Lens Type	fixed focal length
Focal Length	2 mm
Iris Control	DC
Digital Zoom	yes
Horizontal Angle of View	180°
Vertical Angle of View	91°
MOD (Minimum Object Distance)	0,6 m
Illumination	Infrared, White light
Housing	Outdoor
Color (housing)	Pantone P 179-1, RAL9003
Housing material	Aluminium
Heater	no
Blower	no
Video outputs	no
Alarm inputs	nein
Alarm outputs	no
Audio support	yes
Ethernet interface	100Base-TX, 10Base-T
Serial interfaces	Ethernet
Internal storage	256GB, microSDHC card, microSDXC card
Analysis functions	Cross Counting (CC), Heat Map (HM), Human&Vehicle Detection (PD&VD), Line Crossing Detection (LCD), Perimeter Intrusion Detection (PID), Rare Sound Detection (RSD), Stationary Object Detection (SOD)
Mounting	Ceiling mount, Wall mount
Supply voltage	12VDC, PoE
Power consumption	12W
Power over Ethernet	IEEE 802.3af
Vandal proof	no
Operating temperature	-35°C ~ +60°C, @ Humidity 90% or less (non-condensing)
ONVIF	ONVIF Profile G, ONVIF Profile S, ONVIF Profile T
Protection rating	IP67

INB-58F0002M0PA

Continuation of the specifications

Camera type	Bullet
Audio	built-in loudspeaker, built-in microphone
Remote configuration	Browser
Illumination range	approx. 15m, approx. 25m, Infrared, White Light
Weight	350g
Manufacturer order number	238642

Optional Accessory

SKU	Name	Description
233775	AK-21	Camera connection box for Wall and ceiling mounting, IN Series Bullet Cameras
236198	eneo INsight Installation Tool	Supports adjustments for cameras with AI features for IN-series
234990	eneo INsight mobile	Mobile App for recorder IN- and MN-series
218218	eneo Site Manager	Management Software for eneo IP products

Optional Services

SKU	Name	Description
229234	CON-KAM-IPKON	Preconfiguration 1x IP camera Function test, FW update

Your contact person

VIDEOR E. Hartig GmbH
 Carl-Zeiss-Straße 8
 63322 Rödermark
 Germany

