

# Compact Enclosure - MSB

## Manufactured in Europe

### Features

- IP66, IK10 rating
- Powder coated mild steel 1.5mm
- Galvanised mounting plate installed
- Discreet with no external branding or markings
- Reversible door - Hinges on right and left hand side of unit
- Colour - RAL7035
- Earth studs
- Cable management/ runner on the door



### Accessories

- Keyed Lock
- Adjustable pole clamps
- Vented front door, IP54

### Specifications

Model	Sizing(HxWxD)	Description
MSB.202015	200x200x150mm	IP66, 1.5mm Mild steel enclosure
MSB.303020	300x300x200mm	IP66, 1.5mm Mild steel enclosure
MSB.403020	400x300x200mm	IP66, 1.5mm Mild steel enclosure
MSB.403025	400x300x250mm	IP66, 1.5mm Mild steel enclosure
MSB.604020	600x400x200mm	IP66, 1.5mm Mild steel enclosure
MSB.806020	800x600x200mm	IP66, 1.5mm Mild steel enclosure

Model	Description
<b>Vented door for mild steel enclosure</b>	
MSVD.2020	IP54, vented door for MSB.202015 (1x Vent)
MSVD.3030	IP54, vented door for MSB.303020 (1x Vent)
MSVD.4030	IP54, vented door for MSB.403020/25 (2x Vent)
MSVD.6040	IP54, vented door for MSB.604020 (2x Vent)
MSVD.8060	IP54, vented door for MSB.806020 (4x Vent)
<b>Pole Clamps</b>	
BT2-MSG200	Galvanized/Zinc pole clamp for MSB.202015, 100mm to 300mm pole diameter (200 wide cabinet) (150Kgs)
BT2-MSG300	Galvanized/Zinc pole clamp for MSB.303020, 100mm to 300mm pole diameter (300 wide cabinet) (150Kgs)
BT2-MSG400	Galvanized/Zinc pole clamp for MSB.402020/25, 100mm to 300mm pole diameter (400 wide cabinet) (150Kgs)
BT2-MSG600	Galvanized/Zinc pole clamp for MSB.806020, 100mm to 300mm pole diameter (600 wide cabinet) (150Kgs)
<b>Keyed lock</b>	
STP.K2	Chromed keyed lock for MSB and SSB cabinets, (1x for 200-400 high, 2x for 600-800 high)

Specifications are subject to change without prior notice.