

# RG-EW6000GX

## AX6000 Wi-Fi 6 Mesh Router with 2.5G Port



### Highlights

- Ultra-high-speed with Wi-Fi 6 standard (160MHz)
- Quad-core enterprise level chipset
- Max clients up to 384
- Gaming port
- Strong signals received
- Cloud-based Management

# Highlight Features

Full-Power **Wi-Fi 6**

## RG-EW6000GX Steady as Dune, Fast as Wind

RG-EW6000GX with **160 MHz** Channel Bandwidth & **6000 Mbps** Network Speed. Unleash Full-Power Wi-Fi 6 for Accelerated Digital Life.

 2.5 Gbps Port

 Enterprise-Level Quad-Core Chipset

 8 x Antennas

 Gaming Mode



## Select Your Networking with 1 x 2.5 Gbps WAN/LAN Port & 1 x 1 Gbps WAN/LAN Port & 3 x 1 Gbps LAN Ports

### Dual-WAN Aggregation

In dual-WAN aggregation, two Internet connections can achieve a bandwidth exceeding 1.6 Gbps, optimizing network traffic distribution across two ISPs.

Dual-LAN Aggregation

Gaming Port



# Highlight Features

Select Your Networking with 1 x 2.5 Gbps WAN/LAN Port & 1 x 1 Gbps WAN/LAN Port & 3 x 1 Gbps LAN Ports

Dual-WAN Aggregation

Dual-LAN Aggregation

Dual-LAN aggregation allows wired devices to achieve speeds exceeding 1.6 Gbps, significantly supporting high-speed LAN transmission. The RG-EW6000GX is a good helper for vloggers, video creators, video studios.

Gaming Port



Select Your Networking with 1 x 2.5 Gbps WAN/LAN Port & 1 x 1 Gbps WAN/LAN Port & 3 x 1 Gbps LAN Ports

Dual-WAN Aggregation

Dual-LAN Aggregation

Gaming Port


Enable Game Turbo by connecting your computer to the gaming port—prioritizing gaming and critical apps for smooth POS, conferencing, and live streaming. Discover even more features!



## Highlight Features

### Supported by Enterprise-Level 2.0 GHz Quad-Core CPU Chipset

Enjoy better stability under heavy load.  
The RG-EW6000GX demonstrates more stable network performance with multiple connections.



### Support for Concurrent Connections of Multiple Clients

With MU-MIMO technology, the EW6000GX features **8 spatial streams** (2.4 GHz: 4x4, 5 GHz: 4x4), doubles device capacity, and allows for fast and simultaneous connections of different clients without delays.

Up to **384** Clients




# Highlight Features



# Highlight Features

## Manage Your Home Network at Fingertips


Ruijie Reyeer App provides incredible advanced features, allowing you to remotely manage your network at any time.




Network Status Monitoring



Online Client Monitoring



Remote Reboot



Password Changing



# Hardware Specifications

Model	RG-EW6000GX
<b>Wi-Fi Radio</b>	
Operating band	IEEE 802.11b/g/n/ax, 2.400GHz~2.4835GHz; IEEE 802.11a/n/ac/ax, 5.150GHz~5.350GHz; IEEE 802.11a/n/ac/ax, 5.470GHz~5.725GHz; IEEE 802.11a/n/ac/ax, 5.725GHz~5.850GHz;
FEM	iPA
Max. Wi-Fi Speed	2.4 GHz, 1147 Mbps 5 GHz, 4804 Mbps
Maximum transmit power	2.4 GHz: 802.11b:23dBm 802.11g:6M 23dBm; 54M 20dBm 802.11n:MCS0 23dBm MCS7:19dBm 802.11ac:MCS0 23dBm MCS7:19dBm;MCS8 18.5dBm;MCS9 18.5dBm 802.11ax:MCS0 23dBm MCS7:19dBm;MCS11 16.5dBm 5 GHz: 802.11a:6M 23dBm; 54M 19dBm 802.11n:MCS0 23dBm MCS7:19dBm 802.11ac:MCS0 23dBm;MCS9 17dBm (20M/40M/80M) 802.11ax:MCS0 23dBm; MCS9 17dBm (20M/40M/80M) , MCS9 16dBm (160M) ; MCS11 16dBm (20M/40M/80M) MCS11 15dBm (160M) Note: The transmit power varies according to regulations in different countries and regions.
MIMO	2.4 GHz, 4 x 4 5 GHz, 4 x 4
Wi-Fi standard	Wi-Fi 6 (IEEE 802.11 ax)
<b>Antenna</b>	
Antenna	8 x external antennas
Antenna gain (2.4 GHz)	4.5 dBi
Antenna gain (5 GHz)	5.5 dBi
<b>Certification and Regulatory Compliance</b>	
Certification	CE, CB
<b>Dimensions and Weight</b>	

# Hardware Specifications

Model	RG-EW600GX
Product dimensions (W x D x H)	200 mm x 200 mm x 43.8 mm (7.87 in. x 7.87 in. x 1.72 in.) (excluding antennas)
Weight	0.95 kg (2.09 lbs) (without packaging materials) 1.68 kg (3.7 lbs) (with packaging materials)
<b>Environment and Reliability</b>	
Operating humidity	5% RH to 95% RH (non-condensing)
Operating temperature	0 °C to +40 °C (32 °F to 104 °F)
Storage humidity	5% RH to 95% RH (non-condensing)
Storage temperature	-40 °C to +70 °C (-40 °F to 158 °F)
<b>Port Specifications</b>	
LEDs	4 x system status LEDs 1 x Mesh LED
LAN ports	4 x 10/100/1000BASE-T ports
Number of LAN/WAN ports	1 x 10/100/1000BASE-T port
WAN ports	1 x 10/100/1000/2500BASE-T port
<b>Power Supply and Consumption</b>	
Power supply	DC 12 V 2.5 A
<b>Product Information</b>	
Warranty	3 years
<b>System Specifications</b>	
RAM	512 MB

# Software Specifications

Model	RG-EW600GX
<b>Basic Configurations</b>	
LED management	Yes
Internet access mode	PPPoE, DHCP, Static IP, L2TP, WISP
Preconfiguration	Yes
Reset and keep configurations	Yes
Restoring factory defaults	Yes
Configuration backup	Yes
Local upgrade	Yes
Online upgrade	Yes
Scheduled upgrade	No
AP mode	Yes
<b>Ethernet Switching</b>	
WAN port aggregation	Yes
LAN port aggregation	Yes
Specifying the VLAN tag	Yes
<b>IP Service</b>	
Port mapping	Yes
ARP binding	Yes
Number of ARP binding entries	64
DDNS	Yes
No-IP DNS	Yes
Ruijie DDNS	Yes
NAT-DMZ	Yes
Number of port mapping entries	50

# Software Specifications

Model	RG-EW600GX
UPnP	Yes
<b>Behavior Management</b>	
Parental control	Yes
Client access control (based on MAC addresses)	Yes
Client access control (based on time)	Yes
Maximum number of controlled clients	32
Maximum number of parental control policies	32
Selecting clients from the client list to block their access to the Internet	Yes
Specifying MAC addresses of controlled clients	Yes
<b>Ethernet Interface</b>	
MAC address cloning	Yes
VLAN-based IPTV	Yes
<b>Flow Control</b>	
Flow control based on number of users	Yes
Standalone/Shared mode	Yes
Interface flow control	Yes
<b>IPTV/VLAN</b>	
Multiple IPTV ports	Yes
<b>Multicast</b>	
IGMP proxy	Yes
IGMP snooping	Yes
Note: Not supported by wired connections when IPTV is turned on	
<b>Network Management and Monitoring</b>	

# Software Specifications

Model	RG-EW6000GX
Line detection	Yes
Arabic	Yes
Chinese (Hong Kong Traditional)	Yes
Chinese (Simplified)	Yes
English	Yes
Indonesian	Yes
Italian	Yes
Russian	Yes
Spanish (Latin America)	Yes
Thai	Yes
Turkish	Yes
Vietnamese	Yes
Ruijie Cloud management	Yes
Scheduled device restart	Yes
eWeb login password length	8 to 63 characters
Wired repeater mode	Yes
Wireless repeater mode	Yes
WISP mode	Yes
<b>Rate Limiting</b>	
Client-based rate limiting	Yes
<b>Reyee Mesh 3.0</b>	
Reyee Mesh 3.0	Yes
Automatic switching between wired and wireless repeater mode	Yes

# Software Specifications

Model	RG-EW6000GX
Recommended hop count	2
Maximum number of clients	192
Maximum number of devices	32
Security	
Encryption mode	Yes
System Performance Capacity	
Maximum number of concurrent clients	128 (2.4 GHz) 256 (5 GHz)
Recommended number of concurrent clients	16 (2.4 GHz)64 (5 GHz)
IPTV/IGMP client capacity	5
IPTV/IGMP multicast capacity	5
IPTV/IGMP wired forwarding performance	25 Mbps
Recommended camera limit	6 (2.4 GHz) 16 (5 GHz)
VPN	
Number of concurrent tunnels supported by the OpenVPN server	8
Certificate authentication	Yes
OpenVPN bandwidth	13 Mbps
OpenVPN client	Yes
OpenVPN server	Yes
Server domain name configuration	Yes
Username and password authentication	Yes
Number of concurrent tunnels supported by the PPTP VPN server	30
PPTP VPN client	Yes

## Software Specifications

Model	RG-EW6000GX
PPTP VPN server	Yes
Wireless Configuration	
Guest Wi-Fi	Yes
WLAN	
1024-QAM	Yes
MLO	No
DFS	Yes
802.11k/v roaming	Yes
Wi-Fi blocklist capacity	64
SSID hiding	Yes

## Package Contents

Model	RG-EW600GX
<b>Accessories</b>	
Ethernet cable	1
Power adapter	1
<b>Device</b>	
Device	1
<b>Manual</b>	
User Manual	1
Warranty Card	1

*Ruijie* | REYEE

 Redefine your easy network



**Ruijie Networks Co., Ltd.**

Official Website: <https://Reyee.Ruijie.com>